



Dimensions and ratings are subject to change without notice.
Available in all insulation thickness.

Note:

- For welded anchor, see: C1000
- For insulated friction anchor, see: C3000
- For large bore welded anchor, see: C2100
- For insulated positive anchor, see: C4000

Pipe Size	A	Insulation Thickness						
		1"	2"	3"	4"	5"	6"	7"
		B	B	B	B	B	B	B
3	3	4	4	6	6	8	8	10
3.5	3.5	4	4	6	6	8	8	10
4	4	4	4	6	6	8	8	10
5	5	4	4	6	6	8	8	10
6	6	4	4	6	6	8	8	10

Application:

Model C1100 and C1130 are designed for use on:
· Pipe Sizes through 6"

Model No. For use with Pipe Material

C1100	Carbon Steel
C1110	Chrome-Moly
C1120	Carbon Silicon
C1130	Stainless

Features:

- Supplied with bolt holes for choice of bolting or welding to support structure.
- Bottom-of-pipe to top-of-steel matches base mounted insulated supports. See "B" Series.
- Broad selection of materials to match pipe material and eliminate galvanic action.

Material Data:

- **C1100:** A36 Carbon Steel.
- **C1110:** A387 Gr. 22 Chrome-Moly Steel.
- **C1120:** A515 Gr. 70 Carbon Silicon Steel.
- **C1130:** 304L Stainless Steel.
- **Primer Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

Other materials available upon request.

Formal submittal sheets available