



Dimensions and ratings are subject to change without notice.  
Available in all insulation thickness.

Note:

- For welded anchor, see: C2000
- For small bore welded tee "no moment" anchor, see: C1100
- For insulated friction anchor, see: C3000
- For insulated positive anchor, see: C4000

Pipe Size	A	F	G	Insulation Thickness						
				1"	2"	3"	4"	5"	6"	7"
				B	B	B	B	B	B	B
8	6	12	0.38	4	4	6	6	8	8	10
10	6	12	0.38	4	4	6	6	8	8	10
12	6	12	0.38	4	4	6	6	8	8	10
14	6	12	0.38	4	4	6	6	8	8	10
16	6	12	0.38	4	6	6	8	8	10	10
18	9	18	0.5	4	6	6	8	8	10	10
20	9	18	0.5	4	6	6	8	8	10	10
24	9	18	0.5	4	6	6	8	8	10	10
30	12	18	0.5	4	6	6	8	8	10	10

**Application:**

Model C2100 and C2130 are designed for use on:  
· Pipe Sizes through 8" through 30"

Model No.	For use with Pipe Material
C2100	Carbon Steel
C2110	Chrome-Moly
C2120	Carbon Silicon
C2130	Stainless

**Features:**

- Supplied with bolt holes for choice of bolting or welding to support structure.
- Bottom-of-pipe to top-of-steel matches base mounted insulated supports. See "B" Series.
- Broad selection of materials to match pipe material and eliminate galvanic action.

**Material Data:**

- **C2100:** A36 Carbon Steel.
- **C2110:** A387 Gr. 11 Chrome-Moly Steel.
- **C2120:** A515 Gr. 70 Carbon Silicon Steel.
- **C2130:** 304L Stainless Steel.
- **Primer Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

Other materials available upon request.

**Formal submittal sheets available**