



*PSI A-Series Model purchased separately

Insulation and plate sold separately.

Contact factory for pipe, tube sizes, or insulation thicknesses not shown.

Note: For pipe clamps, see: G1000, G1200, G2000, G2200; For shield clamps, see: G1000; For shield guide straps, see: G2000.

Pipe Size	Maximum Lateral Load-Lbs	D-Rod Thread	Insulation Thickness																	
			BARE		1/2		3/4		1		1-1/2		2		2-1/2		3		4	
			A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B	A	B
1/2	50	1/4-20	1.25	2.75	2.5	3.38	2.88	3.63	3.38	3.88	4.5	4.38	5.5	4.88	7.13	5.88	8.13	6.25	10.13	7.25
3/4	50	1/4-20	1.5	3	2.5	3.38	2.88	3.63	3.38	3.88	4.5	4.38	5.5	4.88	7.13	5.88	8.13	6.25	10.13	7.25
1	50	1/4-20	1.75	3	2.88	3.63	3.38	3.88	4	4.25	5	4.63	6.25	5.25	7.13	5.88	8.13	6.25	10.13	7.25
1-1/4	50	3/8-16	2.25	3.5	3.38	4.13	3.38	4.13	4.13	4.38	5.63	5.13	6.25	5.5	7.25	6	8.25	6.50	10.25	7.50
1-1/2	50	3/8-16	2.5	3.63	3.5	4.13	4.13	4.38	4.63	4.63	5.63	5.13	7.25	6	8.25	6.5	9.25	7.00	11.25	8.00
2	50	3/8-16	2.88	3.88	4.13	4.38	4.63	4.63	5.13	4.88	6.25	5.5	7.25	6	8.25	6.5	9.25	7.00	11.25	8.00
2-1/2	50	1/2-13	3.5	4.38	4.88	4.88	5.38	5.13	5.88	5.38	7.5	6.25	8.5	6.75	9.5	7.25	10.50	7.75	12.50	8.75
3	50	1/2-13	4.13	4.63	5.38	5.13	5.88	5.38	6.38	5.63	7.5	6.25	8.5	6.75	9.5	7.25	10.50	7.75	12.50	8.75
3-1/2	50	1/2-13	4.63	4.88	5.88	5.38	6.38	5.75	7.5	6.25	8.5	6.75	9.5	8.63	10.5	7.75	11.50	8.25	13.50	9.25
4	50	1/2-13	5.13	5.13	6.38	5.75	7.5	6.25	7.5	6.25	8.5	6.75	9.5	8.63	10.5	7.75	11.50	8.25	13.50	9.25

TABLE I

Application:

Model G3000 is designed for use on:

- Hot water
- Cold water
- Chilled water
- Dual temperature
- Steam
- Air
- Gas
- Vacuum

Features:

- Easy installation
- Sized to provide approximately 1/16" to 1/8" radial clearance around O.D. of bare pipe or insulated pipe support models A1000 through A7000
- Complete with 4 hex nuts and 4 plain washers
- Other sizes available on request

Material Data:

- **G3000:** Applicable PSI specification document: No.208
- **Steel:** Low carbon threaded rod.
- **Hex Nuts:** ASTM-A-563 Gr. A.
- **Coating:** Primer coating or hot dipped galvanized. Other coatings available upon request.

Formal submittal sheets available